

I. IDENTIFICATION

MANUFACTURED BY: Kryptaglow™
P.O. Box 272672
Tampa, FL 33688

REVISED: 02/11/09

24 Hour Emergency Telephone
CHEMTREC 1-800-424-9300

PRODUCT LINE: Kryptaglow® White Epoxy Base Coat Part B

PROPER SHIPPING NAME: Paint

II. HAZARDOUS INGREDIENTS

Trade Secret		WT%: 20-50	
ACGIH TLV:	ACGIH STEL:		
OSHA PEL:	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE:	LEL%:		
CAS #1330-20-7 Xylene		WT%: 20-50	Footnote: (1)
ACGIH TLV: 100 ppm TWA	ACGIH STEL: 150 ppm		
OSHA PEL: 100 ppm TWA	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE: 6.6mmHg@20C	LEL%: 1.0%		
Trade Secret		WT%: 5-20	Footnote: (1)
ACGIH TLV: N.E.	ACGIH STEL: N.E.		
OSHA PEL: N.E.	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE: <.1mmHg@25C	LEL%: N.E.		
CAS #100-41-4 Ethyl Benzene		WT%: 5-20	
ACGIH TLV: 100 PPM	ACGIH STEL: 125 PPM		
OSHA PEL: 100 PPM	OSHA CEILING:	OSHA PEAK:	
VAPOR PRESSURE:	LEL%:		
CAS #25068-38-6 Bis A, Epchlorhydrn Epoxy		WT%: 1-5	
ACGIH TLV: N.E.	ACGIH STEL: N.E.		
OSHA PEL: N.E.	OSHA CEILING: N.E.	OSHA PEAK: N.E.	
VAPOR PRESSURE: N.E.	LEL%: N.E.		

WARNING MESSAGES:

- (1) Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Chronic exposure may cause damage to the central nervous system, respiratory system, lung, eye, skin, liver, gastrointestinal tract, spleen, kidneys, and blood.
- (2) See Section IX for reportable Hazardous Air Pollutants

III. PHYSICAL DATA

BOILING RANGE: 276-401° F

EVAPORATION RATE: * slower than ether *

PERCENT VOLATILE BY VOLUME: 57.84%

WEIGHT PER GALLON: 7.71 Lbs.

VAPOR DENSITY: * heavier than air *

ACTUAL VOC (lb/gal): 4.19

EPA VOC (lb/gal): 4.19

EPA VOC (g/L): 502.13

IV. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 81° F 27° C

LEL: Refer to Section II

FLAMMABILITY CLASSIFICATION: Class 1C

DOT CLASSIFICATION (HAZARDOUS CLASS): * Flammable Liquid *

EXTINGUISHING MEDIA: Use water spray, dry chemical, foam or Carbon Dioxide. Use water spray to cool fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from heat, sparks, and flame. May generate toxic or irritating combustion products. May generate carbon monoxide or toxic nitrogen gases.

SPECIAL FIRE FIGHTING PROCEDURES: In case of fire and/or explosion do not breathe fumes. Use water spray to reduce vapors. If water pollution occurs, notify appropriate authorities. Wear NIOSH approved self-contained breathing apparatus with independent air supply. Keep containers cool with water spray. Avoid skin contact.

V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE:

ACUTE:

- Eye contact: Severe irritant, chemical burns possible, possible tissue damage. High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.
- Skin contact: Severe irritant, corrosion to tissue, possible skin burns
- Inhalation: Moderate to severe irritant. Minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
- Ingestion: Severe irritation, possible gastrointestinal tract. May cause nausea unless treated promptly.
- CHRONIC: Caused burns to exposed tissue. Xylene contains ethyl benzene which has been classified as a possible carcinogen to humans, Group 2B, by the International Agency for Research on Cancer (IARC), based on sufficient evidence in laboratory animals but inadequate evidence for cancer in humans. Prolonged or repeated overexposure to ethyl benzene may cause the following: kidney effects, liver effects, lung effects, thyroid effects, testicular effects, and pituitary effects. Repeated contact can result in defatted and drying of the skin which may result in skin irritation and dermatitis. Repeated contact with the skin may cause allergic reaction/sensitization. Prolonged inhalation may result in central nervous system depression which may be evidenced by giddiness, headache, dizziness and nausea; in extreme cases, unconsciousness and death may occur. Prolonged exposure to low concentrations of vapor may cause: sore throat, eye irritation, nausea, headache.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Asthma, Chronic respiratory disease (e.g. Bronchitis, Emphysema). Eye disease, Skin disorders and Allergies.

PRIMARY ROUTE(S) OF ENTRY: Ingestion, skin absorption, and inhalation.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult physician.

EYES: Flush immediately with large amounts of water for at least 15 minutes. Talk to a physician for medical treatment.

SKIN: Wipe off with towel. Wash with soap and water. Remove contaminated clothing.

INGESTION: If swallowed, call physician immediately. Remove stomach contents by gastric suction or induce vomiting only as directed by medical personnel. Never give anything by mouth to an unconscious person.

VI. REACTIVITY DATA

STABILITY: * stable *

HAZARDOUS POLYMERIZATION: * will not occur *

INCOMPATIBILITY: Avoid bringing into contact with oxidizing agents, acids, bases or epoxy hardeners under uncontrolled conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide and Nitrogen Oxides in a fire. Nitrogen Oxide can react with water vapors to form corrosive nitric acid (TLV=2 ppm). Combustion of product under oxygen-starved conditions can be expected to produce numerous toxic products including: nitriles, amides. Irritating and toxic fumes at elevated temperatures.

CONDITIONS TO AVOID: Avoid acid contamination and skin contact. Keep containers tightly closed. No smoking or eating in handling area.

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition (flames, hot surfaces and electrical, static or frictional sparks). Avoid breathing vapors. Ventilate area. Use non-sparking tools. Remove with inert absorbent.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: In confined areas of poor ventilation, use chemical cartridge respirator or self-contained breathing apparatus.

VENTILATION: Provide general dilution or local exhaust ventilation in volume and pattern to keep TLV and LEL of most hazardous ingredient in Section II, below acceptable limit.

PROTECTIVE GLOVES: Wear suitable gloves (S37). Nitrile rubber gloves. In emergency situations, wear impermeable gloves with cuffs to prevent spread of material to area above the wrists.

EYE PROTECTION: Splash proof eye goggles. In emergency situations, use eye goggles with a full face shield.

OTHER PROTECTIVE EQUIPMENT: Wear suitable clothing. Long-sleeved clothing.

HYGIENIC PRACTICES: See Section V

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near heat, sparks, flame, strong oxidizing agents or strong acids. This material may cause sensitization. Do not get in eyes, on skin or clothing. Do not allow contaminated clothing to contact skin. Avoid contact with vapors or fumes.

OTHER PRECAUTIONS: Eye wash station and safety shower should be available.

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

INGREDIENT	CAS #	Wt of HAPS in Product	Pounds HAPS/Gal Product
Xylene	1330-20-7	43.6 %	3.4
Ethyl Benzene	100-41-4	9.3 %	0.7

Co-Leash, Inc.
P.O. Box 272672
Tampa, FL 33688
(P) 813/920-1910 (F) 813/792-1418
www.kryptaglow.com